



Telecab

Residential Elevator

OWNER'S MANUAL

(To Be Retained by Owner After Installation by Authorized Savaria Concord Dealer)



©Savaria Concord Lifts Inc. Part no. 000627 (Rev. 06-m03-2008)

IMPORTANT

Ensure that only an authorized Savaria Concord DEALER installs, services, and maintains the TeleCab Residential Elevator. Under no circumstances is anyone other than a Dealer with Savaria Concord training and authorization to install, adjust, service or modify any mechanical or electrical device on this lift. Failure to follow this warning can result in safety systems compromises or defeat; this can result in serious injury or death. Savaria Concord Lifts Inc. accepts no liability for property damage, warranty claims or personal injury, including death, in this circumstance.

Lift and elevator passenger safety is the result of countless details in the equipment's design, manufacture, and installation. After installation, reliable operation and continual safe operation requires regular service and inspection at least twice per year, or more frequently where usage, environment, or local jurisdiction require. As the owner, you're responsible to ensure that regular service and inspections occur in a timely manner.

Refer to this manual for operating instructions, precautions, and for usage of the TeleCab Residential Elevator.

Upon completion of installation, the dealer must provide you with the following information and ensure to record it in this manual; in addition, either the dealer or yourself must keep any service and/or maintenance records in the Maintenance Record section of this manual.

WARRANTY

Ensure your Savaria Concord Dealer provides you with a copy of the manufacturer's limited parts warranty and documentation relating to any Dealer labour warranty.

FOR OWNER'S RECORDS	
Customer Name:	_____
Installing Dealer:	_____
Dealer's Telephone Number:	_____
Date Installed:	_____
Serial/Job Number:	_____



TELECAB RESIDENTIAL ELEVATOR OWNER'S MANUAL

TABLE OF CONTENTS

1.	GENERAL SPECIFICATIONS	4
2.	OPERATION	5
3.	OPTIONAL FEATURES	7
4.	OPERATING THE ELEVATOR FROM THE LANDING CONTROLS	8
5.	OPERATING THE ELEVATOR FROM THE CAB CONTROLS	9
6.	POWER FAILURE AND EMERGENCY LOWERING	10
7.	EMERGENCY LIGHT	10
8.	MANUAL LOWERING	11
9.	MAINTENANCE AND INSPECTION CHECKS	12
10.	MAINTENANCE RECORD	13

1. GENERAL SPECIFICATIONS

TELECAB RESIDENTIAL ELEVATOR	
Load capacity	500 lbs. (227 kg)
Rated speed	25 feet per minute (0.20 mps) (standard)
Tower	8 foot modular guide rail with roller guide shoes
Levels and openings	2 levels and 2 openings
Platform	Non-skid platform surface
Power supply (circuit supplied by others)	110 VAC - 20 amps, single phase
Lighting supply (circuit supplied by others)	120 volt, 60 cycle, 15 amps
Motor	110 VAC, 1.5 HP/screw type
Drive system	2:1 Hydraulic roller chain
Temperature operating range	- 10 °C to + 40 °C / 14 °F to 104 °F
Car access	Enter/exit same side or front/rear Time delay for automatic door lock
Cab size	W30" x L46" x H78" (762 mm x 1,168 mm x 1,981 mm)
Door size	H78" x W30" steel with plexiglass insert
Call stations	Continuous pressure directional push button Keyed call
Emergency lowering	Automatic battery recharging system (115 VAC) Low voltage control
Color and finish	Almond beige or white powder coat
Maximum travel	23 feet, (7.0 m) maximum
Control system	Relay logic
Minimum overhead clearance	90" (2286 mm) conforms to ASME A17.1
Minimum floor cutout	34" x 59" (864 x 1499 mm)
Hall station and control panel finish ????????	clear bronze anodized aluminum (standard) or stainless steel (optional) or brass (optional) rectangular (standard) or oval (optional) hall stations, keyless (standard) or keyed (optional)

2. OPERATION

1) Door Key Switch (Figure 1-A)

The door key switch turns the elevator operation ON and OFF. It limits the use of the elevator to only persons with authorization.

Apply constant pressure on either the UP or DOWN button to

2) Cab Operating Panel Buttons (Figure 1-B)

Automatic Control

The Automatic Control Panel buttons facilitate the UP/DOWN movement of the cab between landings. After pressing a landing button, the cab automatically moves to the landing.

The cab stops once it arrives at the landing.

3) Door Open Button (Figure 1-C)

The elevator door/gate closes automatically after a pre-set adjustable time of 8 seconds.

Press the door open button to open the door/gate once the cab is at a landing.

5) Alarm Button (Figure 1-D)

Press the Alarm button to sound the alarm in case of an emergency.

4) Emergency Stop Button (Figure 1-E)

Press the Emergency Stop button to **Stop** the cab and activate the alarm buzzer at any time.

6) Handrail

A single handrail is on the Cab Operating Panel side of the cab.

7) Emergency Light

The cab emergency light remains ON in the event of a main power failure. The emergency light uses a Battery Back-Up system and includes an automatic recharger.

8) Landing Hall Call Station Controls

Hall Call Stations at all landings initiate the movement of the cab to the landing. An optional key switch limits the elevator's use to only persons with authorization.

9) Landing Door and/or Gate Interlock

The Landing Door/Gate lock prevents cab movement unless the door/gate is in the shut position with the lock in place. If the door/gate is not completely shut, the cab does not move.



Figure 2 Hall Call Station

10) Emergency Battery Operation

In the event of a building power failure, the door/gate system includes a temporary power back up system to continue the opening operation a number of times. Upon resuming normal building power, the back up system turns OFF and automatically recharges.

3. OPTIONAL FEATURES

Automatic Door Opener

- a) Press the Landing Hall Call button to call the elevator. The entrance door opens automatically once the elevator stops at the landing.
- b) Press the Remote Control (if equipped) to open the entrance door once the elevator stops at the landing.
- c) Push 'n' Go allows the entrance door to open automatically with a slight push to the door itself. The door timer is inoperative when this feature is active.

Automatic Gate Opener

- a) Press the Landing Hall Call button to call the elevator. The Gate opens automatically once the elevator stops at the landing and the entrance door is fully open.
- b) Manually open the entrance door. The Gate opens automatically once the entrance door is fully open.

NOTE

If the cab is equipped with a gate, the gate must be closed after exiting the cab. If the gate is left open, all controls will remain inoperable.

An "entry" and "exit" timer allows approximately nine seconds before the hall buttons become operational. This delay allows time for a person to enter/exit the cab.

4. OPERATING THE ELEVATOR FROM THE LANDING CONTROLS

Automatic Operation

- 1) Insert the key (if equipped) into the switch on the Hall Call and turn the key to the ON position.
- 2) Press the Hall Call button once and release. The elevator automatically comes to your landing.
- 3) Turn the key (if equipped) to the OFF position and remove the key.
- 4) If required, turn the door handle and pull the door open.
- 5) If the cab includes a manual gate, slide the gate open and enter the cab.
- 6) Once inside the cab, close the gate, insert the key (if equipped) into the key switch, and turn the key to the ON position.

NOTE

When using the landing controls, the cab can only be moved (called) to the level from which you are calling. When using the control buttons in the cab, the cab can be moved to any level.



WHEELCHAIR WHEELS MUST BE LOCKED AT ALL TIMES WHEN THE ELEVATOR IS MOVING

5. OPERATING THE ELEVATOR FROM THE CAB CONTROLS

Automatic Operation

- 1) Insert the key (if equipped) into the switch in the Cab Operating Panel. Turn the key to the ON position.
- 2) Press a Floor Landing button once and release. The elevator automatically travels to and stops at the Floor Landing.
- 3) Turn the key (if equipped) to the OFF position and remove the key.
- 4) Unlock the wheelchair wheels and exit the cab (if applicable).

NOTE

If the cab is equipped with a gate, the gate must be closed after exiting the cab. If the gate is left open, all controls will remain inoperable.

An "entry" and "exit" timer allows approximately nine seconds before the hall buttons become operational. This delay allows time for a person to enter/exit the cab.

6. POWER FAILURE AND EMERGENCY LOWERING

In the event of a power failure, the elevator includes a Battery Back-Up system that allows the user to lower the elevator from inside of the cab itself; this device operates on batteries and activates only if a main power supply failure occurs. The following steps describe this operational sequence:

- 1) For elevators with **automatic operation**, press any Floor Landing button below the floor where the elevator currently rests.
- 2) Upon arrival at the floor, the landing door automatically unlocks.
- 3) If the door includes an automatic gate, the gate opens.
- 4) Remove the key, open the manual gate, (if equipped) and exit the cab.

7. EMERGENCY LIGHT

In the event of a main power failure, the emergency cab lights automatically illuminate.

8. MANUAL LOWERING

In the event of a power failure, batteries lower the cab to the next level and open the doors. Should the batteries fail, use the telephone to call for help. A technician can use the “Manual Hand Crank” to lower the elevator.

- 1) Instruct the person(s) in the elevator to remain calm and to stay well back from the door of the elevator. Ease their concern by telling them your intentions.
- 2) Turn the “Main Disconnect Switch” to the “OFF” position.
- 3) Locate the “Motor Access Door”; insert the Manual Hand Crank” onto the motor shaft, and crank the elevator to the next lowest level.
- 4) Use the “Emergency Key” to open the elevator door.
- 5) To exit the cab, open the lower landing door and assist the passenger(s).

9. MAINTENANCE AND INSPECTION CHECKS

Regular maintenance keeps the Eclipse in proper operating condition. Please remember, as the owner of this elevator, you are responsible to ensure that maintenance and upkeep occurs on a consistent and regular basis. To ensure the continual proper operating condition of your unit, have a technician inspect the following items and, if necessary, service the elevator every six (6) months. The elevator may require additional inspections, depending on usage.

- 1) Tighten all rail and cab fastening bolts.
- 2) Lubricate the door hinges and adjust the door closure, if required.
- 3) Lubricate the rails with light grease, such as white lithium.
- 4) Inspect the travelling cable for wear. Replace if any cuts or damage to the jacket are evident.
- 5) Replace the batteries inside the control panel as indicated on the battery label.

To perform maintenance to the Kiklock (if equipped), call your Authorized Savaria Concord Dealer.

Telecab
Owner's Manual
Part no. 000627 rev:4/09
©Copyright, 2009

Savaria Concord Lifts, Inc.
www.savariaconcord.com
107 Alfred Kuehne Blvd.
Brampton, Ontario, L6T 4K3, Canada

